

**DULUX**  
**CONTRACT EMULSION PAINT**

**A965-LINE (WATERBORNE)**

**PRODUCT INFORMATION**

PRODUCT NAME	CONTRACT EMULSION PAINT
PRODUCT CODE	A965 Line
DESCRIPTION	<b>Contract Emulsion Paint</b> is an economical emulsion paint with a smooth matt finish needs.
USAGE	<b>Contract Emulsion Paint</b> is suitable for all masonry surfaces including brickwork, plaster, cement, asbestos as well as hard and soft wallboards.
BENEFITS	Smooth matt finish
PACK SIZE	20 litres only
COLOUR RANGE	Refer appropriate colour card





**PERFORMANCE GUIDE**

FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand moderately vigorous washing.
THEORETICAL COVERAGE	The spreading capacity of this product will vary considerably according to the roughness and porosity of the surface. On smooth surfaces of average porosity 9 – 10 m <sup>2</sup> /litre.










**PRODUCT DATA**

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Blinder : PVA Emulsion. Solvent : Water.
VOLUME SOLIDS	White 30% (nominal), other colours will vary.



















**APPLICATION**

THINNING Brush or Roller Conventional Spray Airless Spray	For normal use, thinning should not exceed 25% Thin up to 30% Ready for use.
SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°.
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: Dependant on temperature and humidity. 1- 2 hours.
CLEANING UP	Clean all equipment with clean water immediately after use.
	 Application method  65° spraying tip  1-2 hours drying time  Practise proper cleaning

**PRE - APPLICATION**

SURFACE PREPARATION	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off.								
SYSTEM INFORMATION Powdery Surfaces  Alkaline and New Surfaces  Normal, Sound Surfaces	<table border="0"> <tr> <td>PRIMER (1 COAT)</td> <td>FINISH (2 COATS)</td> </tr> <tr> <td><b>Dulux</b> Adhesion Promoting Interior Wall Primer (A579 – 15458)</td> <td></td> </tr> <tr> <td><b>Dulux</b> Alkali Resisting Interior Wall Sealer (A931 – 18380)</td> <td><b>Dulux</b> Contract Emulsion (A965)</td> </tr> <tr> <td>No Primer Required.</td> <td></td> </tr> </table>	PRIMER (1 COAT)	FINISH (2 COATS)	<b>Dulux</b> Adhesion Promoting Interior Wall Primer (A579 – 15458)		<b>Dulux</b> Alkali Resisting Interior Wall Sealer (A931 – 18380)	<b>Dulux</b> Contract Emulsion (A965)	No Primer Required.	
PRIMER (1 COAT)	FINISH (2 COATS)								
<b>Dulux</b> Adhesion Promoting Interior Wall Primer (A579 – 15458)									
<b>Dulux</b> Alkali Resisting Interior Wall Sealer (A931 – 18380)	<b>Dulux</b> Contract Emulsion (A965)								
No Primer Required.									
	<table border="0"> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>Ensure good surface profile</td> <td>Blast cleaning</td> <td>Seal a coat with primer</td> </tr> </table>				Ensure good surface profile	Blast cleaning	Seal a coat with primer		
									
Ensure good surface profile	Blast cleaning	Seal a coat with primer							

**PRECAUTION**

SAFETY, HEALTHY AND ENVIRONMENTAL INFORMATION	<p>May cause sensitisation by skin contact.          Avoid contact with skin.          In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.          To remove splashes of paint from skin, use soap and water or a recognised cleanser.          Keep away from food, drinks, animal feed and out of the reach of children.          Container must be stored in a cool and shaded place.          It must be tightly closed in a secure, upright position.          Work in a well-ventilated area and do not breathe in vapour or spray.          A suitable mask should be worn during sanding.          When applying paint, it is advisable to wear eye protection and suitable gloves.          In case of a spillage, contain and collect spillage using sand or earth and do not empty into watercourses, drains or the environment.          Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.          Refer to <b>Maxilite</b> Trade Product Safety Data Sheet for further details.          In case of emergency, refer to Emergency Incident Response Hotline 1800 80 6187.</p>												
	<table border="0"> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>Keep seal tight</td> <td>Store in cool place</td> <td>Secure upright</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>Wear proper protection</td> <td>Ensure good ventilation</td> <td>Practise proper disposal</td> </tr> </table>				Keep seal tight	Store in cool place	Secure upright				Wear proper protection	Ensure good ventilation	Practise proper disposal
													
Keep seal tight	Store in cool place	Secure upright											
													
Wear proper protection	Ensure good ventilation	Practise proper disposal											