

DULUX

HEAT RESISTING ALUMINIUM FINISH

A338-2554 (HIGH PERFORMANCE-SOLVENTBORNE)

PRODUCT INFORMATION

PRODUCT NAME	Dulux Heat Resisting Aluminium Finish
PRODUCT CODE	A338-2554
DESCRIPTION	Dulux Heat Resisting Aluminium Finish is a special fast drying solvent-based paint.
USAGE	Suitable for use on both interior and exterior smooth or textured masonry, wood, and metal surfaces.
BENEFITS	Gives an exceptionally bright lustre with excellent durability.
PACK SIZE	5 litres only.
COLOUR RANGE	Aluminium.




PERFORMANCE GUIDE

FILM PROPERTIES Chemical Resistance Heat Resistance Water Resistance	Resistant to mild chemical fume attack but where there is heavy attack, e.g. actual contact with chemicals, a specialist paint system may be required. Generally resistant to heat up to 350°C. Resistant to the levels of atmospheric humidity present in normal interior and exterior environments and will withstand repeated washing. Not suitable for use on immersed surfaces.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 15-21.2 m ² /L.



PRODUCT DATA

COMPOSITION (nominal)	Pigment : Non-Leafing Aluminium. Blinder : Alkyd. Solvent : White Spirit.
VOLUME SOLIDS	53% (nominal).
FLASH POINT	22°C.

APPLICATION

THINNING Brush or Roller Conventional Spray	Ready for use, thinning is usually not necessary. Ready for use.
SPRAY RECOMMENDATIONS Conventional Spray	Satisfactory through most equipment.
Drying TIMES Touch Dry Recoat	Single coat at standard thickness: 4-6 hours 6 hours.
CLEANING UP	Clean all equipment with Dulux Thinner 850-11 immediately after use.
FILM THICKNESS	Wet: 50-65 micro-metres. Dry: 25-35 micro-metres.
	 Application method
	 4-6 hours drying time
	 Practise proper cleaning

PRE - APPLICATION

SURFACE PREPARATION	Surfaces generally must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dusted off. Surfaces should be manually prepared by power or hand tool to BS 7079 Part A1: 1989 St3.		
SYSTEM INFORMATION	PRIMER (1 COAT) No primer required	UNDERCOAT (1 COAT) No undercoat required	FINISH (2 COATS) Dulux Heat Resisting Aluminium Finish (A338 - 2554)
	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Use abrasive paper</p> </div> <div style="text-align: center;">  <p>Dust off</p> </div> </div>		

PRECAUTION

SAFETY, HEALTHY AND ENVIRONMENTAL INFORMATION	<p>FLAMMABLE</p> <p>Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>Repeated exposure may cause skin dryness or cracking.</p> <p>Contains: ETHYL METHYL KETOXIME. May produce an allergic reaction.</p> <p>In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</p> <p>To remove splashes of paint from skin, use soap and water or a recognised cleanser.</p> <p>If swallowed seek medical advice immediately and show this container or label.</p> <p>Keep away from food, drinks, animal feed and out of the reach of children.</p> <p>Keep away from combustible material.</p> <p>Container must be stored in a cool and shaded place.</p> <p>It must be tightly closed in a secure, upright position.</p> <p>Work in a well-ventilated area and do not breathe in vapour or spray. A suitable mask should be worn during sanding</p> <p>When applying paint, it is advisable to wear eye protection and suitable gloves</p> <p>In case of fire use foam, dry powder, AFFF, CO2 – Never use water.</p> <p>In case of a spillage, contain and collect spillage using sand or earth and do not empty into watercourses, drains or the environment.</p> <p>Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.</p> <p>Refer to Dulux Product Safety Data Sheet for further details.</p> <p>In case of emergency, refer to Emergency Incident Response Hotline 1800 80 6187.</p>
---	---

	 FLAMMABLE	 Keep seal tight	 Store in cool place	
	 Secure upright	 Wear proper protection	 Ensure good ventilation	 Practise proper disposal