

**DULUX PEARL GLO**  
LUXURY WALL FINISH

**A913 LINE (WATERBORNE)**

**PRODUCT INFORMATION**

PRODUCT NAME	<b>Dulux</b> Pearl Glo Luxury Wall Finish
PRODUCT CODE	A913 Line
DESCRIPTION	<b>Dulux</b> Pearl Glo Wall Finish is a premium quality, highly durable and washable emulsion with a mid sheen finish.
USAGE	<b>Dulux</b> Pearl Glo is suitable for all normal interior wall and ceiling surfaces but is not suitable for use in areas subject to frequent or heavy condensation as in some kitchens and bathrooms.
BENEFITS	Highly washable surfaces. Gives an attractive mid sheen finish that exudes the shimmers and luxury of pearls.
PACK SIZE	1 litre and 5 litres.
COLOUR RANGE	Refer to <b>Dulux</b> Colour Inspirations.





**PERFORMANCE GUIDE**

FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand moderately vigorous washing. Not suitable where frequent heavy condensation is likely, as in kitchens and bathrooms.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 10.5 - 11.5m <sup>2</sup> /litre




**PRODUCT DATA**

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Blinder : PVA Copolymer Emulsion. Solvent : Water.
VOLUME SOLIDS	White 35% (nominal), other colours will vary







**APPLICATION**

THINNING Brush or Roller  Conventional Spray Airless Spray	For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (20%). For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%). Add up to 1 part of clean water to 5 parts of paint (20%). Ready for use.
SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140Kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: Dependant on temperature and humidity. 1- 2 hours.
CLEANING UP	Clean all equipment with clean water immediately after use.
	 Application method  65° spraying tip  1-2 hours drying time  Practise proper cleaning

**PRE - APPLICATION**

SURFACE PREPARATION	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Primer (see below).	
SYSTEM INFORMATION Powdery Surfaces  Alkaline and New Surfaces  Normal, Sound Surfaces	<b>PRIMER (1 COAT)</b> <b>Dulux</b> Adhesion Promoting Interior Wall Primer (A579 – 15458) <b>Dulux</b> Alkali Resisting Interior Wall Sealer (A931 – 18380) No Primer Required.	<b>FINISH (2 COATS)</b>  <b>Dulux</b> Pearl Glo Emulsion (A913)
	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">                       Use abrasive paper                 </div> <div style="text-align: center;">                       Dust off                 </div> <div style="text-align: center;">                       Seal a coat with primer                 </div> </div>	

**PRECAUTION**

SAFETY, HEALTHY AND ENVIRONMENTAL INFORMATION	<p>In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.                      To remove splashes of paint from skin, use soap and water or a recognised cleanser.                      Keep away from food, drinks, animal feed and out of the reach of children.                      Container must be stored in a cool and shaded place.                      It must be tightly closed in a secure, upright position.                      Work in a well-ventilated area and do not breathe in vapour or spray.                      A suitable mask should be worn during sanding.                      When applying paint, it is advisable to wear eye protection and suitable gloves.                      In case of a spillage, contain and collect spillage using sand or earth and do not empty into watercourses, drains or the environment.                      Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.                      Refer to <b>Dulux</b> Product Safety Data Sheet for further details.                      In case of emergency, refer to Emergency Incident Response Hotline 1800 80 6187.</p>	
	<div style="display: grid; grid-template-columns: repeat(3, 1fr); gap: 10px;"> <div style="text-align: center;">                       Keep seal tight                 </div> <div style="text-align: center;">                       Store in cool place                 </div> <div style="text-align: center;">                       Secure upright                 </div> <div style="text-align: center;">                       Wear proper protection                 </div> <div style="text-align: center;">                       Ensure good ventilation                 </div> <div style="text-align: center;">                       Practise proper disposal                 </div> </div>	