

DULUX
ROAD LINE PAINT

A432 LINE (HIGH PERFORMANCE-SOLVENTBORNE)

PRODUCT INFORMATION

PRODUCT NAME	Dulux Road Line Paint	
PRODUCT CODE	A432 Line	
DESCRIPTION	Dulux Road Line Paint is used for marking the bitumen and concrete roads.	
USAGE	Suitable for interior and exterior use, marking car parks, demarcation zones etc. on concrete and asphalt surfaces.	
BENEFITS	Rapid drying properties which allow road markings to be resistant to vehicular traffic after 30-45 minutes Excellent adhesion and durability	
PACK SIZE	5 litres only.	
COLOUR RANGE	PJ-0173 Non-reflective White PJ-0174 Non-reflective Yellow PJ-0232 Non-reflective Black	15145 Reflective Yellow 16073 Reflective Yellow

PERFORMANCE GUIDE

FILM PROPERTIES	
Chemical Resistance	Not recommended where spillage of solvents is likely.
Chemical Resistance	Good
Water Resistance	Good
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 9m ² /L.

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Lightfast Pigments and Mineral extenders. (Glass Beads in the case of reflective versions.) Blinder : Modified Epoxy Ester. Solvent : Aromatic Hydrocarbon.
VOLUME SOLIDS	60% (nominal).
FLASH POINT	Below 22°C.

APPLICATION

THINNING Brush or Roller Road Marking Machine	For normal use, thinning is usually not necessary. If required, add up to 1 part of Dulux Thinner 850-11 to 10 parts of paint (10%). Add up to 1 part of Dulux Thinner 850-11 to 10 parts of paint (10%).
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: Normally touch dry after 15 minutes and resistant to vehicular traffic after 30-45 minutes. After 30 minutes.
CLEANING UP	Clean all equipment with Dulux Thinner 850-11 immediately after use.

PRE - APPLICATION

SURFACE PREPARATION	Surfaces must be sound, clean, dry, free from all defective or poorly adhering material, dirt, grease etc. Due to the variability of asphalt, newly laid bitumen based surfaces (up to six months old) will need to be sealed with a coat of emulsion paint or shellac knotting, in order to prevent bleeding. A test area is recommended before work is commenced.	
SYSTEM INFORMATION Powdery Surfaces	PRIMER (1 COAT) No primer required	FINISH (1 OR 2 COATS) Dulux Road Line Paint (A432 Line)

PRECAUTION

SAFETY, HEALTHY AND ENVIRONMENTAL INFORMATION	<p>In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes of paint from skin, use soap and water or a recognised cleanser. Keep away from food, drinks, animal feed and out of the reach of children. Container must be stored in a cool and shaded place. It must be tightly closed in a secure, upright position. Work in a well-ventilated area and do not breathe in vapour or spray. A suitable mask should be worn during sanding. When applying paint, it is advisable to wear eye protection and suitable gloves. In case of a spillage, contain and collect spillage using sand or earth and do not empty into watercourses, drains or the environment. Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations. Refer to Dulux Product Safety Data Sheet for further details. In case of emergency, refer to Emergency Incident Response Hotline 1800 80 6187.</p>	
---	--	--

	<div style="display: flex; flex-wrap: wrap; justify-content: space-around;"> <div style="text-align: center; margin: 5px;">  Keep seal tight </div> <div style="text-align: center; margin: 5px;">  Store in cool place </div> <div style="text-align: center; margin: 5px;">  Secure upright </div> <div style="text-align: center; margin: 5px;">  Wear proper protection </div> <div style="text-align: center; margin: 5px;">  Ensure good ventilation </div> <div style="text-align: center; margin: 5px;">  Practise proper disposal </div> </div>					
--	--	--	--	--	--	--