

**DULUX ROOF PAINT
HIGH SHEEN FINISH**

A311 LINE (SOLVENTBORNE)

PRODUCT INFORMATION

PRODUCT NAME	Dulux Roof Paint High Sheen Finish
PRODUCT CODE	A311-Line
DESCRIPTION	Dulux Roof Paints is a high quality, highly “durable solvent-based roof paint” which gives a high sheen finish.
USAGE	It is specially designed for the protection and decoration of old and new roofs including asbestos, cement, zinc, and galvanised iron roofs.
BENEFITS	Rejuvenates aged tiles with a glossy look. Excellent colour fastness.
PACK SIZE	5 litres only.
COLOUR RANGE	PJ-0053 Red and PJ-0054 Green.

PERFORMANCE GUIDE

FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in exterior environments.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 13 m ² /L.

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Light Fast Non-Lead Pigments and Mineral Extenders. Blinder : Alkyd. Solvent : White Spirit.
VOLUME SOLIDS	50% (nominal), other colours will vary.
FLASH POINT	32°C – 55°C.

APPLICATION

THINNING Brush or Roller Conventional Spray Airless Spray	Ready for use, thinning is usually not necessary. Add up to 1 part of Dulux Thinner 850 – 41 or white spirit to 5 parts of paint (20%). Ready for use.
SPRAY RECOMMENDATIONS Conventional Spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application is a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.43mm (17 thou) and a spray tip angle of 65°.
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: 4 – 6 hours under normal conditions. 12 hours under normal conditions.
CLEANING UP	Clean all equipment with Dulux Thinner 850 – 41 or white spirit immediately after use.
FILM THICKNESS	Wet: 70 micro – metres. Dry: 35 micro – metres.

	<p>gloves.</p> <p>In case of fire use foam, dry powder, AFFF, CO2 – Never use water.</p> <p>In case of a spillage, contain and collect spillage using sand or earth and do not empty into watercourses, drains or the environment.</p> <p>Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.</p> <p>Refer to Dulux Product Safety Data Sheet for further details.</p> <p>In case of emergency, refer to Emergency Incident Response Hotline 1800 80 6187.</p>																
	<table border="0"> <tr> <td data-bbox="619 591 730 696"></td> <td data-bbox="804 591 916 696"></td> <td data-bbox="979 591 1091 696"></td> <td></td> </tr> <tr> <td data-bbox="619 696 730 725">FLAMMABLE</td> <td data-bbox="804 696 916 748">Keep seal tight</td> <td data-bbox="979 696 1091 748">Store in cool place</td> <td></td> </tr> <tr> <td data-bbox="619 786 730 891"></td> <td data-bbox="804 786 916 891"></td> <td data-bbox="979 786 1091 891"></td> <td data-bbox="1155 786 1267 891"></td> </tr> <tr> <td data-bbox="619 891 730 943">Secure upright</td> <td data-bbox="804 891 916 943">Wear proper protection</td> <td data-bbox="979 891 1091 943">Ensure good ventilation</td> <td data-bbox="1155 891 1267 965">Practise proper disposal</td> </tr> </table>					FLAMMABLE	Keep seal tight	Store in cool place						Secure upright	Wear proper protection	Ensure good ventilation	Practise proper disposal
FLAMMABLE	Keep seal tight	Store in cool place															
Secure upright	Wear proper protection	Ensure good ventilation	Practise proper disposal														