

DULUX

SILICONE WATER REPELLENT SOLUTION

A285-LINE (SOLVENTBORNE)

PRODUCT INFORMATION

PRODUCT NAME	Dulux Silicone Water Repellent Solution
PRODUCT CODE	A285 – Line
DESCRIPTION	Dulux Silicone Water Repellent Solution is a solvent based transparent treatment solution.
USAGE	Suitable for use on both interior and exterior fairface masonry surface both new and old, such as brickwork, concrete, stucco and other masonry materials.
BENEFITS	Excellent water repellency and penetration
PACK SIZE	5 litres only.
COLOUR RANGE	19025 Clear and 14057 Red.

PERFORMANCE GUIDE

THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 2 – 4 m ² /L depending on the absorbency of the surface.
----------------------	--

PRODUCT DATA

COMPOSITION (nominal)	Pigment : N/A Blinder : Oligomeric Siloxane. Solvent : White Spirit.
VOLUME SOLIDS	5% (nominal).
FLASH POINT	32 ^o C – 55 ^o C.

APPLICATION

THINNING Brush or Roller Conventional Spray	Ready for use. Ready for use.
SPRAY RECOMMENDATIONS Conventional Spray	When applying by spray, a low pressure should be used so that the solution emerges from the gun in an easy stream.
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: Dependant on temperature and humidity. 4 hours
CLEANING UP	Clean all equipment with Dulux Thinner 850 – 41 or white spirit immediately after use.



Application method





4 hours recoat time



Practise proper cleaning

PRE - APPLICATION

SURFACE PREPARATION	All surfaces should be thoroughly prepared by vigorous scraping and brushing to remove any loose particles and dirt. A stiff fibre brush will give better results than a wire brush, as any wire that becomes embedded in the wall will rust, and stain the new paint. All mould or organic growth on the masonry should be removed. For large areas a water jet is recommended. The area should then be treated with Dulux Fungicidal Wash. Minor faults or imperfections in the surface can be made good using a suitable grade of exterior filler. Larger holes or cracks should be filled with a sand and cement mix.	
SYSTEM INFORMATION Normal Sound Surfaces	PRIMER (1 COAT) Dulux Silicone Water Repellent Solution (A285)	FINISH (1 OR 2 COATS) Dulux Silicone Water Repellent Solution (A285) Dulux Weathershield (A910)
	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Use abrasive paper</p> </div> <div style="text-align: center;">  <p>Dust off</p> </div> </div>	

PRECAUTION

SAFETY, HEALTHY AND ENVIRONMENTAL INFORMATION	<p>FLAMMABLE</p> <p>Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>Repeated exposure may cause skin dryness or cracking.</p> <p>Avoid contact with skin.</p> <p>In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</p> <p>To remove splashes of paint from skin, use soap and water or a recognised cleanser.</p> <p>If swallowed seek medical advice immediately and show this container or label.</p> <p>Keep away from food, drinks, animal feed and out of the reach of children.</p> <p>Keep away from combustible material.</p> <p>Container must be stored in a cool and shaded place.</p> <p>It must be tightly closed in a secure, upright position.</p> <p>Work in a well-ventilated area and do not breathe in vapour or spray.</p> <p>A suitable mask should be worn during sanding.</p> <p>When applying paint, it is advisable to wear eye protection and suitable gloves.</p> <p>In case of fire use foam, dry powder, AFFF, CO₂ – Never use water.</p> <p>In case of a spillage, contain and collect spillage using sand or earth and do not empty into watercourses, drains or the environment.</p> <p>Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.</p> <p>Refer to Dulux Product Safety Data Sheet for further details.</p> <p>In case of emergency, refer to Emergency Incident Response Hotline 1800 80 6187.</p>
---	---

	 FLAMMABLE	 Keep seal tight	 Store in cool place	
	 Secure upright	 Wear proper protection	 Ensure good ventilation	 Practise proper disposal