

DULUX TIMBERCOLOUR
ACRYLIC WOOD FINISH

A926 LINE (WATERBORNE)

PRODUCT INFORMATION

PRODUCT NAME	Dulux Timbercolour Acrylic Wood Finish
PRODUCT CODE	A926 Line
DESCRIPTION	Dulux Timbercolour Acrylic Wood Finish is a highly quality, durable emulsion ideal for direct application to exterior wood surfaces.
USAGE	Dulux Timbercolour Acrylic Wood Finish is ideal for direct application to exterior wood surfaces including fences, barge-boards, fascias, exposed balconies, wood walls and cladding. This can also be used direct onto galvanised iron such as gutters and roof sheets.
BENEFITS	Excellent adhesion properties and durability. Contains light-fast pigments which give a good colour fastness. Works as an effective mould control.
PACK SIZE	5 litres only.
COLOUR RANGE	Refer to Dulux Colour Inspirations.




PERFORMANCE GUIDE

FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in exterior environments.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 10 – 11 m ² /litre.




PRODUCT DATA

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Emulsion. Solvent : Water.
VOLUME SOLIDS	35% (nominal), other colours will vary.







APPLICATION

THINNING Brush or Roller	For normal use, thinning is usually not necessary. If required, add up to 1 part of clean water to 10 parts of paint (10%).
Conventional Spray	Add up to 1 part of clean water to 3 parts of paint (30%).
SPRAY RECOMMENDATIONS	Satisfactory through most equipment.
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: Dependant on temperature and humidity. 2 - 3hours.
CLEANING UP	Clean all equipment with clean water immediately after use.
	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Application method</p> </div> <div style="text-align: center;">  <p>2-3 hours recoat time</p> </div> <div style="text-align: center;">  <p>Practise proper cleaning</p> </div> </div>

PRE - APPLICATION

SURFACE PREPARATION	Surfaces must be sound, clean, as dry as possible and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper in the direction of the grain and dusted off. Clean all of dirt, mould, algae, lichen or moss with a wire brush. On badly affected areas treat with Dulux Fungicidal Wash .	
SYSTEM INFORMATION	PRIMER (1 COAT) N/A	FINISH (2 COATS) Dulux Timbercolour Acrylic Wood Finish (A926)
	 <p>Use abrasive paper</p>	 <p>Dust off</p>
	 <p>Treat with Dulux Wash Fungicidal</p>	

PRECAUTION

SAFETY, HEALTHY AND ENVIRONMENTAL INFORMATION	<p>In case of contact with eyes, rinse immediately with plenty of water and seek medical advice</p> <p>To remove splashes of paint from skin, use soap and water or a recognised cleanser.</p> <p>Keep away from food, drinks, animal feed and out of the reach of children.</p> <p>Container must be stored in a cool and shaded place</p> <p>It must be tightly closed in a secure, upright position</p> <p>Work in a well-ventilated area and do not breathe in vapour or spray</p> <p>A suitable mask should be worn during sanding</p> <p>When applying paint, it is advisable to wear eye protection and suitable gloves</p> <p>In case of a spillage, contain and collect spillage using sand or earth and do not empty into water courses, drains or the environment</p> <p>Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations</p> <p>Refer to Dulux Product Safety Data Sheet for further details</p> <p>In case of emergency, refer to Emergency Incident Response Hotline 1800 80 6187.</p>		
	 <p>Keep seal tight</p>	 <p>Store in cool place</p>	 <p>Secure upright</p>
	 <p>Wear proper protection</p>	 <p>Ensure good ventilation</p>	 <p>Practise proper disposal</p>